




STROKE 70 30W



Product Description

The extruded aluminum housing with die cast end caps offers a precise in-line appearance. This LED fixture comes with excellent light distribution, high wired electronic ballast and mounting clamps to be used in surface & suspended application. Available in white, grey & black

Mechanical Design Parameters

| | |
|-------------------|---------------------|
| Shape | Rectangle |
| Dimension | 1200mm x 70mm x90mm |
| Mounting Aiming | Surface/Suspended |
| Finish | Powder Coated |
| IP Rating | 20 |

Electrical Parameters

| | |
|---|----------------------------------|
| lamp Type Lamp Base | LED |
| Type Of driver / Transformer / Control Gear | Constant Current Isolated Driver |
| Voltage Range | 180-270V |
| Input frequency | 50 Hz |
| Electrical Class | UL class 2 |
| T Ambient T max | 50°C / 85°C max |
| Max THD System Power Factor | THD ≤ 10%, PF≥0.9 |

Optical/Photometric Parameter

| | |
|-----------------------------------|----------------|
| Color Temperature / Color Of Lamp | 3000/4000/6000 |
| Optics | Diffuser |
| Min. CRI | 80 |
| Lamp Life Expectancy | 50000 hours |
| Expected System Lumen | 80 |
| Expected Total Lumen | 2400 |